

This concealed camera is specially designed for high level security or concealed monitoring applications such as bank, ATM machine, airport, museum, detective, spy and home security.

The outlook design was just like an ordinary spot light. Meanwhile, the front cover was made from a patented high-tech material which can not be seen through by human eyes, yet can be seen through by camera. Therefore, it will be hardly recognized as a camera.

Feature

- ▶ Camera lens covered by the special patented front cover
- ▶ Ceiling mount spot light outlook with camera embedded
- ▶ Easy adjustable view angle
- ▶ 1/3" color CCD sensor for clear video output



	INT-CMC-M2	INT-CMC-H2
Scanning System	NTSC : 525 lines 2:1 interlace ; PAL : 625 lines 2:1 interlace	
Scanning Frequency	NTSC : 15,734Hz(H) , 60Hz(V) ; PAL : 15,625Hz(H), 50Hz(V)	
Effective Pixel	NTSC : 510(H) x 492(V) PAL : 500(H) x 582(V)	NTSC : 768(H) x 494(V) PAL : 752(H) x 582(V)
Electronic Shutter	NTSC : 1/60-100,000sec. ; PAL : 1/50-100,000sec.	
Image Device	1/3" SONY Super HAD CCD	
Horizontal Resolution	420 TV lines	520 TV lines
Sensitivity	0.2Lux	
Signal to Noise	More than 48dB	
Gain Control	AGC	
White Balance	Auto 2500-9500oK	
BLC	Auto	
Gamma Correction	0.45	
SYNC System	Internal	
Lens/Focus point	3.6mm (Optional 4.3mm, 6mm]	
Video Output	1.0 Vp-p 75 Ohm	
Power Requirement(±10%)	DC12V	
Power Consumption(±10%)	100mA	
Operation Temp.	Working: -10~+50oC, Storage: -30~+70oC, Humidity:0~95%RH	
Dimension(mm)	Ø128 x 84	

Weight(N.W)

0.28kg

