

This concealed camera is specially designed for high level security or concealed monitoring applications such as bank, ATM machine, airport, museum, detective, spy and home security. The outlook design is a dome type camera with mirror dome cover. The view angle of this camera will not be noticed by people.

Feature

- ▶ Camera lens covered by the special patented dome cover
- ▶ Easy installation
- ▶ 1/3" color CCD sensor for clear video output



	INT-CMD-M	INT-CMD-H
Scanning System	NTSC : 525 lines 2:1 interlace ; PAL : 625 lines 2:1 interlace	
Scanning Frequency	NTSC : 15,734Hz(H) , 60Hz(V) ; PAL : 15,625Hz(H) , 50Hz(V)	
Effective Pixel	NTSC : 510(H) x 492(V) PAL : 500(H) x 582(V)	NTSC : 768(H) x 494(V) PAL : 752(H) x 582(V)
Electronic Shutter	NTSC : 1/60-100,000sec. ; PAL : 1/50-100,000sec.	
Image Device	1/3" SONY Super HAD CCD	
Horizontal Resolution	420 TV lines	520 TV lines
Sensitivity	0.2Lux	
Signal to Noise	More than 48dB	
Gain Control	AGC	
White Balance	Auto 2500-9500oK	
BLC	Auto	
Gamma Correction	0.45	
SYNC System	Internal	
Lens/Fousc point	3.6mm (Optional 4.3mm, 6mm)	
Video Output	1.0 Vp-p 75 Ohm	
Power Requirement(±10%)	DC12V	
Power Consumption(±10%)	100mA	
Operation Temp.	Working: -10~+50oC, Storage: -30~+70oC, Humidity:0~95%RH	
Dimension(mm]	Ø110 x 90	
Weight(N.W]	235g	

