

4CH Standalone DVR Package

From €599.00

(VAT inclusive)

Offer for a limited time only!



PLUS



Internet Connection / mobile phone access

- (1) XGA Output
- (2) Video Output: BNC x 1
- (3) Video IN: BNC x 4
- (4) Audio Input: RCA x 1, Line-In
- (5) Audio Output: RCA x 1, Line-Out
- (6) Power Input: For safety reasons, always use the original factory power adaptor attached.
Adaptor : DC-12V / 3A
- (7) LAN Output: (Optional)
- (8) DEFAULT : Reset to factory setting.

FEATURES

- 1 - Triplex (Recording, Playback, Network simultaneously).
- 2 - Up to 60fps Recording Speed.
- 3 - USB flash disk backup.
- 4 - Adjust Up/Down/Left/Right screen position.
- 5 - Video Input Signal: NTSC / PAL.
- 6 - Video Compression: Modified MJPEG.
- 7 - Manual, Motion, & Programmed.
- 8 - Motion Detection with Adjustable Time Duration.
- 9 - Search Data by Date and Time.
- 10 - Power Recover Auto Restore Record Mode.
- 11 - Hard Disk LED Indicator When Recording.
- 12 - Motion Detection.
- 13 - Audio Recording.
- 14 - SATA Hard Disk.
- 15 - Remote Control.
- 16 - XGA Output
- 17 - LAN (Optional).

SPECIFICATIONS

Model Number	INT-468LX		
Video Format	NTSC/PAL		
Operating System	Embedded RTOS		
VGA Output	D-SUB 15Pin VGA		
Video Input	BNC x 4 (1Vp-p 75Ω)		
Audio Input	RCA x 1, Line-In		
Video Output	BNC x 1(Main Monitor)		
Audio Output	RCA x 1, Line-Out		
Language	Multi-Language		
Display Frame	NTSC	120 fps (4 × 30 fps)	
	PAL	100 fps (4 × 25 fps)	
Recording Frame (EACH)	NTSC	Max. 60 fps	
	PAL	Max. 50 fps	
Video Operation	Triplex (Record, Playback, Internet Access)		
Resolution	Display	NTSC	640 x 448
		PAL	640 x 544
	Recording	NTSC	640x224
		PAL	640x272
Compression Format	Modified MJPEG	Normal	12K Bytes / Frame
		High	15K Bytes / Frame
		Highest	20K Bytes / Frame
HDD	SATA HDD x 1		
Backup	USB		
Search	Mode	Time/Date/Event	
Motion Detect	Full screen	Yes	
Loss Detect		Yes	
Auto Switching		Yes	
Buzzer Output		Yes	
Brightness Adjust		Yes	
Contrast Adjust		Yes	
VGA Output	640*480/800*600/1024*768/1280*1024		
System Monitor	Power Recover Auto Restore Record Mode		
Web Transmission Format	MPEG4		
Power Supply	DC 12V / 3A(AC100V~240V 50/60HZ)		
Dimension	220mm x 228mm x 48mm (WxDxH)		
Weight	1.5KG		

Package price include 2 outdoor tube cameras: Sharp 420TVL, 5X23PCS IR LED working distance: 20M, 3.6mm/F2.0 board lens, and 2 indoor plastic IR dome; Sharp 420TVL, 5X23PCS IR LED working distance: 20M, 3.6mm/F2.0 board lens and 1 250GB SATA harddrive.

Price and specifications are subject to change without prior notice.



E-mail: info@genitronics.com; <http://www.genitronics.com>, www.genitronics.be